



金属化聚丙烯膜电容器(浸渍型) Metallized polypropylene film capacitor(dipped)

■ 外形图 Outline Drawing

	Forming Lead Shapes			
	I	II	III	IV
	P ≥ F		P < F	
	0mm < P-F ≤ 3mm	3mm < P-F ≤ 8mm	3mm < F-P ≤ 5mm	0mm < F-P ≤ 3mm
	F ± 0.8mm; A ≤ 5.0mm; B=4.5 ± 0.5mm			

■ 特点

- 金属化聚丙烯膜
- 高频损耗小
- 内部温升小
- 阻燃环氧粉末包封 (UL94/V-0)

■ 主要用途

- 广泛应用于高频、直流、交流和脉冲电路中
- 适用于要求体积小，性能优异的彩电 S 校正电路
- 专为大屏幕显视器及彩电的 S 校正电路设计
- 适用于各种高频、大电流场合

■ Features

- Metallized polypropylene film
- Low loss at high frequency
- Small inherent temperature rise
- Flame retardant epoxy resin powder coating (UL94/V-0)

■ Typical application

- Widely used in high frequency, DC, AC and pulse circuits
- Providing optimum performance with small size in S-correction circuits for colour TV set
- Specially designed for S-correction circuits of large screen monitor and colour TV
- Suitable for the situation where applies high frequency and high current pulse

■ 技术要求 Specifications

引用标准 Reference Standard	GB/T 14579(IEC 60384-17)						
气候类别 Climatic Category	40/105/21						
额定温度 Rated Temperature	85℃						
工作温度 Operating Temperature Range	-40℃ ~ 105℃ (+85℃ to +105℃: decreasing factor 1.25% per °C for U _R)						
额定电压 Rated Voltage	100V、160V、250V、400V、630V、1 000V、1 250V						
电容量范围 Capacitance Range	0.0010μF ~ 3.3μF						
电容量偏差 Capacitance Tolerance	± 5%(J)、± 10%(K)、± 20%(M)						
耐电压 Voltage Proof	1.6U _R (5s)						
损耗角正切 Dissipation Factor	≤ 10 × 10 ⁻⁴ (1kHz, 20℃)						
绝缘电阻 Insulation Resistance	≥ 100 000MΩ, C _N ≤ 0.33μF ≥ 30 000s, C _N > 0.33μF (20℃, 100V, 1min)						
最大脉冲爬升速率 Maximum Pulse Rise Time(dV/dt): 若实际工作电压 U 比额定电压 U _R 低, 电容器可工作在更高的 dV/dt 场合, 这样 dv/dt 允许值应为右表值乘以 U _R /U。 If the working voltage(U) is lower than the rated voltage(U _R),the capacitor can be worked at a higher dV/dt. In this case, the maximum allowed dV/dt is obtain by multiplying the right value with U _R /U.	Pattern I						
	U _R (V)	dV/dt (V/μs)					
		P=7.5	P=10.0	P=15.0	P=20.0	P=25.0	P=30.0
	100/160	180	150	110	80	60	--
	200/250	660	560	310	150	110	--
	400	900	780	600	300	180	120
	630	1 500	1 200	900	400	220	150
	1 000	2 500	2 200	--	--	--	--
	Pattern II						
	U _R (V)	dV/dt (V/μs)					
		P=7.5	P=10.0	P=15.0	P=22.5		
	100/250	660	560	310	130		
400	900	780	600	300			
630	1 500	1 200	900	400			
1 000/1 250	2 500	2 200	--	--			

产品编码说明 Part number system

■ 18位产品代码如下:

The 18 digits part number is formed as follow:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
C	3	1															

第1~3位	型号代码 C31= CBB21	Digit 1 to 3	Series code C31= CBB21
第4~5位	直流额定电压 2A=100V 2C=160V 2D=200V 2E=250V 2G=400V 2J=630V 3A=1 000V 3B=1 250V	Digit 4 to 5	D.C. rated voltage 2A=100V 2C=160V 2D=200V 2E=250V 2G=400V 2J=630V 3A=1 000V 3B=1 250V
第6~8位	标称容量 举例: 103=10 × 10 ³ pF=0.01μF	Digit 6 to 8	Rated capacitance value For example: 103=10 × 10 ³ pF=0.01μF
第9位	容量偏差 J= ± 5%,K= ± 10%,M= ± 20%	Digit 9	Capacitance tolerance J= ± 5%,K= ± 10%,M= ± 20%
第10位	引线脚距P 3=7.5mm 4=10.0mm 5=12.5mm 6=15.0mm 8=20.0mm 9=22.5mm A=25.0mm C=30.0mm	Digit 10	Pitch 3=7.5mm 4=10.0mm 5=12.5mm 6=15.0mm 8=20.0mm 9=22.5mm A=25.0mm C=30.0mm
第11位	内部特征码 S=II 型	Digit 11	Internal use S= Pattern II
第12~15位	引线加工和包装代码	Digit 12 to 15	Lead form and packaging code
第16~18位	内部特征码	Digit 16 to 18	Internal use

■ Table 1 引线加工和包装代码 lead form and packaging code

第 12 位 Digit 12		第 13 位 Digit 13		第 14 位 Digit 14		第 15 位 Digit 15	
代码 Code	说明 explanation	代码 Code	说明 explanation	代码 Code	说明 explanation	代码 Code	说明 explanation
A	弹带包装 ammo-pack	3	F=7.5mm	1	表示弯脚 kinked	A	产品在连续的两个载带孔之间 each cap. between two consecutive holes P3=12.7mm,H=20.0mm (For pitch=7.5mm)
		4	F=10.0mm			E	P3=25.4mm;H=20.0mm (For pitch=10.0/15.0mm)
		6	F=15.0mm				(Detail parameter refer to pag 18)
F	引线成型 lead kinked	4	F=10.0mm	0	B=4.5mm (the length of B)	0	B 的长度偏差 ±0.5mm B Length tolerance ± 0.5mm
		6	F=15.0mm				
		7	F=17.5mm				
		8	F=20.0mm				
		9	F=22.5mm				
Y	直脚 straight lead "Y" in the figure above	代码 Code	说明 explanation	0		0	引线长度偏差 ±0.5mm Length tolerance ± 0.5mm
		45	引线长度 4.5mm lead length 4.5mm				
第 12-15 位代码为 "C000" 表示标准的引线长度 (20mm ~ 30mm) Digit 12-15 code "C000" means standard lead length (20mm ~ 30mm)							



C31
CBB21 series

■ 外形尺寸 Dimensions (mm)
Pattern II (Reduced sizes)

100Vdc(63Vac)/250Vdc(160Vac) [#]						
C _N (μF)	W max	H max	T max	P	d	Part number
0.010	9.8	7.7	4.0	7.5	0.6	C312A103-3S****++
0.011	9.8	7.8	4.2	7.5	0.6	C312A113-3S****++
0.012	9.8	7.9	4.3	7.5	0.6	C312A123-3S****++
0.013	9.8	8.0	4.4	7.5	0.6	C312A133-3S****++
0.015	9.8	7.8	4.2	7.5	0.6	C312A153-3S****++
0.016	9.8	7.9	4.3	7.5	0.6	C312A163-3S****++
0.018	9.8	8.1	4.4	7.5	0.6	C312A183-3S****++
0.020	9.8	8.2	4.6	7.5	0.6	C312A203-3S****++
0.022	9.8	8.4	4.8	7.5	0.6	C312A223-3S****++
0.024	9.8	8.6	4.9	7.5	0.6	C312A243-3S****++
0.027	9.8	7.6	4.0	7.5	0.6	C312A273-3S****++
0.030	9.8	7.7	4.1	7.5	0.6	C312A303-3S****++
0.033	9.8	7.9	4.2	7.5	0.6	C312A333-3S****++
0.036	9.8	8.0	4.4	7.5	0.6	C312A363-3S****++
0.039	9.8	8.1	4.5	7.5	0.6	C312A393-3S****++
0.043	9.8	8.3	4.7	7.5	0.6	C312A433-3S****++
0.047	9.8	8.5	4.8	7.5	0.6	C312A473-3S****++
0.051	12.3	8.0	4.3	10.0	0.6	C312A513-4S****++
0.056	12.3	8.1	4.5	10.0	0.6	C312A563-4S****++
0.062	12.3	8.3	4.6	10.0	0.6	C312A623-4S****++
0.068	12.3	8.5	4.8	10.0	0.6	C312A683-4S****++
0.075	12.3	8.6	5.0	10.0	0.6	C312A753-4S****++
0.082	12.3	8.8	5.2	10.0	0.6	C312A823-4S****++
0.091	12.3	8.1	4.5	10.0	0.6	C312A913-4S****++
0.10	12.3	8.3	4.7	10.0	0.6	C312A104-4S****++
0.11	12.3	8.5	4.8	10.0	0.6	C312A114-4S****++
0.12	12.3	8.6	5.0	10.0	0.6	C312A124-4S****++
0.13	12.3	8.6	4.9	10.0	0.6	C312A134-4S****++
0.15	12.3	8.9	5.2	10.0	0.6	C312A154-4S****++
0.16	12.3	9.0	5.4	10.0	0.6	C312A164-4S****++
0.18	12.3	9.3	5.6	10.0	0.6	C312A184-4S****++
0.20	12.3	9.5	5.9	10.0	0.6	C312A204-4S****++
0.22	12.3	9.8	6.1	10.0	0.6	C312A224-4S****++
0.24	12.3	10.0	6.4	10.0	0.6	C312A244-4S****++
0.27	17.5	10.5	5.3	15.0	0.6	C312A274-6S****++
0.30	17.5	10.8	5.5	15.0	0.6	C312A304-6S****++
0.33	17.5	11.0	5.8	15.0	0.6	C312A334-6S****++
0.36	17.5	11.2	6.0	15.0	0.6	C312A364-6S****++
0.39	17.5	11.4	6.2	15.0	0.6	C312A394-6S****++
0.43	17.5	11.6	6.4	15.0	0.6	C312A434-6S****++
0.47	17.5	11.9	6.6	15.0	0.6	C312A474-6S****++
0.51	17.5	12.1	6.9	15.0	0.6	C312A514-6S****++
0.56	17.5	12.4	7.2	15.0	0.6	C312A564-6S****++
0.62	17.5	12.7	7.5	15.0	0.8	C312A624-6S****++
0.68	17.5	13.5	7.8	15.0	0.8	C312A684-6S****++
0.75	17.5	13.9	8.2	15.0	0.8	C312A754-6S****++
0.82	17.5	14.2	8.5	15.0	0.8	C312A824-6S****++
0.91	17.5	14.9	8.9	15.0	0.8	C312A914-6S****++
1.0	17.5	15.0	9.3	15.0	0.8	C312A105-6S****++
1.1	17.5	15.5	9.7	15.0	0.8	C312A115-6S****++
1.2	25.2	14.8	7.5	22.5	0.8	C312A125-9S****++
1.3	25.2	15.1	7.8	22.5	0.8	C312A135-9S****++
1.5	25.2	15.6	8.3	22.5	0.8	C312A155-9S****++
1.6	25.2	15.9	8.6	22.5	0.8	C312A165-9S****++
1.8	25.2	16.4	9.1	22.5	0.8	C312A185-9S****++
2.0	25.2	16.9	10.1	22.5	0.8	C312A205-9S****++
2.2	25.2	18.3	9.9	22.5	0.8	C312A225-9S****++
2.4	25.2	18.7	10.4	22.5	0.8	C312A245-9S****++
2.7	25.2	19.3	10.9	22.5	0.8	C312A275-9S****++
3.0	25.2	19.9	11.6	22.5	0.8	C312A305-9S****++
3.3	25.2	20.5	12.1	22.5	0.8	C312A335-9S****++

400Vdc(200Vac)						
C _N (μF)	W max	H max	T max	P	d	Part number
0.010	9.8	7.8	4.1	7.5	0.6	C312G103-3S****++
0.011	9.8	7.9	4.2	7.5	0.6	C312G113-3S****++
0.012	9.8	8.0	4.4	7.5	0.6	C312G123-3S****++
0.013	9.8	8.1	4.5	7.5	0.6	C312G133-3S****++
0.015	9.8	8.4	4.7	7.5	0.6	C312G153-3S****++
0.016	9.8	8.5	4.8	7.5	0.6	C312G163-3S****++
0.018	9.8	8.7	5.0	7.5	0.6	C312G183-3S****++
0.020	9.8	8.9	5.3	7.5	0.6	C312G203-3S****++
0.022	9.8	9.1	5.5	7.5	0.6	C312G223-3S****++
0.024	12.3	8.0	4.3	10.0	0.6	C312G243-4S****++
0.027	12.3	8.1	4.5	10.0	0.6	C312G273-4S****++
0.030	12.3	8.3	4.7	10.0	0.6	C312G303-4S****++
0.033	12.3	8.5	4.8	10.0	0.6	C312G333-4S****++
0.036	12.3	8.6	5.0	10.0	0.6	C312G363-4S****++
0.039	12.3	8.7	5.0	10.0	0.6	C312G393-4S****++
0.043	12.3	8.8	5.2	10.0	0.6	C312G433-4S****++
0.047	12.3	9.0	5.4	10.0	0.6	C312G473-4S****++
0.051	12.3	9.2	5.6	10.0	0.6	C312G513-4S****++
0.056	12.3	9.4	5.8	10.0	0.6	C312G563-4S****++
0.062	12.3	8.9	5.2	10.0	0.6	C312G623-4S****++
0.068	12.3	9.1	5.4	10.0	0.6	C312G683-4S****++
0.075	12.3	9.3	5.7	10.0	0.6	C312G753-4S****++
0.082	12.3	9.5	5.9	10.0	0.6	C312G823-4S****++
0.091	12.3	9.8	6.1	10.0	0.6	C312G913-4S****++
0.10	12.3	10.0	6.4	10.0	0.6	C312G104-4S****++
0.11	12.3	10.3	6.6	10.0	0.6	C312G114-4S****++
0.12	17.5	10.7	5.5	15.0	0.6	C312G124-6S****++
0.13	17.5	10.9	5.7	15.0	0.6	C312G134-6S****++
0.15	17.5	11.2	6.0	15.0	0.6	C312G154-6S****++
0.16	17.5	11.3	6.1	15.0	0.6	C312G164-6S****++
0.18	17.5	11.6	6.4	15.0	0.6	C312G184-6S****++
0.20	17.5	11.9	6.7	15.0	0.6	C312G204-6S****++
0.22	17.5	12.2	7.0	15.0	0.6	C312G224-6S****++
0.24	17.5	12.5	7.3	15.0	0.6	C312G244-6S****++
0.27	17.5	12.9	7.6	15.0	0.8	C312G274-6S****++
0.30	17.5	13.7	8.0	15.0	0.8	C312G304-6S****++
0.33	17.5	14.1	8.4	15.0	0.8	C312G334-6S****++
0.36	17.5	14.4	8.7	15.0	0.8	C312G364-6S****++
0.39	17.5	14.7	9.0	15.0	0.8	C312G394-6S****++
0.43	17.5	15.1	9.4	15.0	0.8	C312G434-6S****++
0.47	17.5	15.5	9.8	15.0	0.8	C312G474-6S****++
0.51	25.2	14.8	7.6	22.5	0.8	C312G514-9S****++
0.56	25.2	15.2	7.9	22.5	0.8	C312G564-9S****++
0.62	25.2	15.6	8.3	22.5	0.8	C312G624-9S****++
0.68	25.2	15.9	9.1	22.5	0.8	C312G684-9S****++
0.75	25.2	16.3	9.6	22.5	0.8	C312G754-9S****++
0.82	25.2	16.7	10.0	22.5	0.8	C312G824-9S****++
0.91	25.2	17.2	10.5	22.5	0.8	C312G914-9S****++
1.0	25.2	17.7	10.9	22.5	0.8	C312G105-9S****++

备注: 1. “-”表示容量偏差。 “-”=capacitance tolerance code, M=±20%,K=±10%,J=±5%
 2. “****”表示引线加工和包装代码(见表1)。“****”=lead form and packing code (refer to table 1)
 3. “#”当额定电压为250Vdc时,第4~5位是2E。“#”when the rated voltage is 250Vdc,the digit 4~5 is 2E.

■ 外形尺寸 Dimensions (mm)
Pattern II (Reduced sizes)

630Vdc(220Vac) [@]							630Vdc(220Vac) [@]							1 000/1 250Vdc [#] (400Vac)						
C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number
0.0010	10.0	7.9	4.3	7.5	0.6	C312J102-3S****++	0.027	12.3	9.4	5.7	10.0	0.6	C312J273-4S****++	0.0010	10.0	7.9	4.3	7.5	0.6	C313A102-3S****++
0.0011	10.0	8.1	4.4	7.5	0.6	C312J112-3S****++	0.030	12.3	9.6	6.0	10.0	0.6	C312J303-4S****++	0.0011	10.0	8.1	4.4	7.5	0.6	C313A112-3S****++
0.0012	10.0	8.2	4.5	7.5	0.6	C312J122-3S****++	0.033	12.3	9.9	6.2	10.0	0.6	C312J333-4S****++	0.0012	10.0	8.2	4.5	7.5	0.6	C313A122-3S****++
0.0013	10.0	8.3	4.7	7.5	0.6	C312J132-3S****++	0.036	12.3	10.1	6.4	10.0	0.6	C312J363-4S****++	0.0013	10.0	8.3	4.7	7.5	0.6	C313A132-3S****++
0.0015	10.0	8.1	4.4	7.5	0.6	C312J152-3S****++	0.039	12.3	10.3	6.7	10.0	0.6	C312J393-4S****++	0.0015	10.0	8.1	4.4	7.5	0.6	C313A152-3S****++
0.0016	10.0	8.2	4.5	7.5	0.6	C312J162-3S****++	0.043	17.5	10.7	5.4	15.0	0.6	C312J433-6S****++	0.0016	10.0	8.2	4.5	7.5	0.6	C313A162-3S****++
0.0018	10.0	7.8	4.2	7.5	0.6	C312J182-3S****++	0.047	17.5	10.8	5.6	15.0	0.6	C312J473-6S****++	0.0018	10.0	7.8	4.2	7.5	0.6	C313A182-3S****++
0.0020	10.0	8.0	4.3	7.5	0.6	C312J202-3S****++	0.051	17.5	11.0	5.8	15.0	0.6	C312J513-6S****++	0.0020	10.0	8.0	4.3	7.5	0.6	C313A202-3S****++
0.0022	10.0	8.1	4.5	7.5	0.6	C312J222-3S****++	0.056	17.5	11.2	6.0	15.0	0.6	C312J563-6S****++	0.0022	10.0	8.1	4.5	7.5	0.6	C313A222-3S****++
0.0024	9.8	8.0	4.3	7.5	0.6	C312J242-3S****++	0.062	17.5	11.4	6.2	15.0	0.6	C312J623-6S****++	0.0024	10.0	7.7	4.0	7.5	0.6	C313A242-3S****++
0.0027	9.8	8.1	4.5	7.5	0.6	C312J272-3S****++	0.068	17.5	11.7	6.5	15.0	0.6	C312J683-6S****++	0.0027	10.0	7.8	4.2	7.5	0.6	C313A272-3S****++
0.0030	9.8	8.3	4.7	7.5	0.6	C312J302-3S****++	0.075	17.5	11.9	6.7	15.0	0.6	C312J753-6S****++	0.0030	10.0	8.0	4.4	7.5	0.6	C313A302-3S****++
0.0033	9.8	8.5	4.8	7.5	0.6	C312J332-3S****++	0.082	17.5	12.2	7.0	15.0	0.6	C312J823-6S****++	0.0033	10.0	8.2	4.5	7.5	0.6	C313A332-3S****++
0.0036	9.8	8.0	4.4	7.5	0.6	C312J362-3S****++	0.091	17.5	12.5	7.3	15.0	0.6	C312J913-6S****++	0.0036	10.0	8.3	4.7	7.5	0.6	C313A362-3S****++
0.0039	9.8	8.2	4.5	7.5	0.6	C312J392-3S****++	0.10	17.5	12.8	7.6	15.0	0.8	C312J104-6S****++	0.0039	10.0	8.4	4.8	7.5	0.6	C313A392-3S****++
0.0043	9.8	8.3	4.7	7.5	0.6	C312J432-3S****++	0.11	17.5	13.6	7.9	15.0	0.8	C312J114-6S****++	0.0043	10.0	8.2	4.5	7.5	0.6	C313A432-3S****++
0.0047	9.8	8.5	4.9	7.5	0.6	C312J472-3S****++	0.12	17.5	13.9	8.2	15.0	0.8	C312J124-6S****++	0.0047	10.0	8.3	4.7	7.5	0.6	C313A472-3S****++
0.0051	9.8	8.6	5.0	7.5	0.6	C312J512-3S****++	0.13	17.5	14.2	8.5	15.0	0.8	C312J134-6S****++	0.0051	10.0	8.5	4.8	7.5	0.6	C313A512-3S****++
0.0056	9.8	8.8	5.2	7.5	0.6	C312J562-3S****++	0.15	17.5	14.7	9.0	15.0	0.8	C312J154-6S****++	0.0056	10.0	8.7	5.0	7.5	0.6	C313A562-3S****++
0.0062	9.8	9.0	5.4	7.5	0.6	C312J622-3S****++	0.16	17.5	15.0	9.3	15.0	0.8	C312J164-6S****++	0.0062	10.0	8.7	5.0	7.5	0.6	C313A622-3S****++
0.0068	12.3	8.0	4.4	10.0	0.6	C312J682-4S****++	0.18	17.5	15.5	9.8	15.0	0.8	C312J184-6S****++	0.0068	12.0	8.9	5.2	10.0	0.6	C313A682-4S****++
0.0075	12.3	8.2	4.5	10.0	0.6	C312J752-4S****++	0.20	17.5	16.0	10.3	15.0	0.8	C312J204-6S****++	0.0075	12.0	9.1	5.4	10.0	0.6	C313A752-4S****++
0.0082	12.3	8.3	4.7	10.0	0.6	C312J822-4S****++	0.22	25.2	15.2	7.9	22.5	0.8	C312J224-9S****++	0.0082	12.0	9.3	5.6	10.0	0.6	C313A822-4S****++
0.0091	12.3	8.5	4.9	10.0	0.6	C312J912-4S****++	0.24	25.2	15.5	8.2	22.5	0.8	C312J244-9S****++	0.0091	12.0	9.5	5.9	10.0	0.6	C313A912-4S****++
0.010	12.3	7.8	4.1	10.0	0.6	C312J103-4S****++	0.27	25.2	15.9	9.2	22.5	0.8	C312J274-9S****++	0.010	12.0	9.9	6.3	10.0	0.6	C313A103-4S****++
0.011	12.3	7.9	4.2	10.0	0.6	C312J113-4S****++	0.30	25.2	16.4	9.6	22.5	0.8	C312J304-9S****++							
0.012	12.3	8.0	4.4	10.0	0.6	C312J123-4S****++	0.33	25.2	16.8	10.0	22.5	0.8	C312J334-9S****++							
0.013	12.3	8.1	4.5	10.0	0.6	C312J133-4S****++	0.36	25.2	17.2	10.4	22.5	0.8	C312J364-9S****++							
0.015	12.3	8.3	4.7	10.0	0.6	C312J153-4S****++	0.39	25.2	17.6	10.8	22.5	0.8	C312J394-9S****++							
0.016	12.3	8.5	4.8	10.0	0.6	C312J163-4S****++	0.43	25.2	18.1	11.3	22.5	0.8	C312J434-9S****++							
0.018	12.3	8.6	4.9	10.0	0.6	C312J183-4S****++	0.47	25.2	18.6	11.8	22.5	0.8	C312J474-9S****++							
0.020	12.3	8.8	5.1	10.0	0.6	C312J203-4S****++	0.51	25.2	19.0	12.2	22.5	0.8	C312J514-9S****++							
0.022	12.3	8.9	5.3	10.0	0.6	C312J223-4S****++	0.56	25.2	19.6	12.8	22.5	0.8	C312J564-9S****++							
0.024	12.3	9.1	5.5	10.0	0.6	C312J243-4S****++														

备注: 1. “-”表示容量偏差。 “-” =capa citance tolerance code, M= ± 20%,K= ± 10%,J= ± 5%
 2. “****”表示引线加工和包装代码(见表1)。“****” =lead form and packing code (refer to table 1)
 3. “#”当额定电压为1250Vdc时,第4~5位是3B。“#” when the rated voltage is 1250Vdc,the digit 4 ~ 5 is 3B.
 4. “@” Not suitable for across-the-line applications. Pls refer to interference Suppression Capacitors (Pag. 118)



C31
CBB21 series

■ 外形尺寸 Dimensions (mm)
Pattern I (High performance)

100Vdc(63Vac)/160Vdc(90Vac)#							250Vdc(160Vac)							400Vdc(200Vac)						
C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number
0.010	10.0	10.0	6.0	7.5	0.6	C312A103-30****+	0.010	10.0	10.0	6.0	7.5	0.6	C312E103-30****+	0.010	10.0	10.0	6.0	7.5	0.6	C312G103-30****+
0.011	10.0	10.0	6.0	7.5	0.6	C312A113-30****+	0.011	10.0	10.0	6.0	7.5	0.6	C312E113-30****+	0.011	10.0	10.0	6.0	7.5	0.6	C312G113-30****+
0.012	10.0	10.5	6.5	7.5	0.6	C312A123-30****+	0.012	10.0	10.5	6.5	7.5	0.6	C312E123-30****+	0.012	10.0	10.5	6.5	7.5	0.6	C312G123-30****+
0.013	10.0	10.5	6.5	7.5	0.6	C312A133-30****+	0.013	10.0	9.0	6.5	7.5	0.6	C312E133-30****+	0.013	10.0	10.5	6.5	7.5	0.6	C312G133-30****+
0.015	10.0	11.0	7.0	7.5	0.6	C312A153-30****+	0.015	10.0	9.5	6.0	7.5	0.6	C312E153-30****+	0.015	10.0	11.0	7.0	7.5	0.6	C312G153-30****+
0.016	10.0	11.0	7.0	7.5	0.6	C312A163-30****+	0.016	10.0	9.5	6.0	7.5	0.6	C312E163-30****+	0.016	10.0	11.0	7.0	7.5	0.6	C312G163-30****+
0.018	10.0	11.0	7.5	7.5	0.6	C312A183-30****+	0.018	10.0	10.0	6.0	7.5	0.6	C312E183-30****+	0.018	10.0	11.0	7.5	7.5	0.6	C312G183-30****+
0.020	10.0	9.0	5.0	7.5	0.6	C312A203-30****+	0.020	10.0	9.0	5.0	7.5	0.6	C312E203-30****+	0.020	10.0	11.5	7.5	7.5	0.6	C312G203-30****+
0.022	10.0	9.0	5.5	7.5	0.6	C312A223-30****+	0.022	10.0	9.0	5.5	7.5	0.6	C312E223-30****+	0.022	10.0	12.0	8.0	7.5	0.6	C312G223-30****+
0.024	10.0	9.0	5.5	7.5	0.6	C312A243-30****+	0.024	10.0	9.5	5.5	7.5	0.6	C312E243-30****+	0.024	13.0	10.5	6.5	10.0	0.6	C312G243-40****+
0.027	10.0	9.5	5.5	7.5	0.6	C312A273-30****+	0.027	10.0	9.5	5.5	7.5	0.6	C312E273-30****+	0.027	13.0	12.0	6.5	10.0	0.6	C312G273-40****+
0.030	10.0	9.5	6.0	7.5	0.6	C312A303-30****+	0.030	10.0	9.5	6.0	7.5	0.6	C312E303-30****+	0.030	13.0	12.0	6.5	10.0	0.6	C312G303-40****+
0.033	10.0	10.0	6.0	7.5	0.6	C312A333-30****+	0.033	10.0	10.0	6.0	7.5	0.6	C312E333-30****+	0.033	13.0	12.0	7.0	10.0	0.6	C312G333-40****+
0.036	10.0	10.0	6.0	7.5	0.6	C312A363-30****+	0.036	10.0	10.0	6.0	7.5	0.6	C312E363-30****+	0.036	13.0	12.5	7.0	10.0	0.6	C312G363-40****+
0.039	10.0	10.0	6.5	7.5	0.6	C312A393-30****+	0.039	10.0	10.0	6.5	7.5	0.6	C312E393-30****+	0.039	13.0	12.5	7.0	10.0	0.6	C312G393-40****+
0.043	10.0	10.5	6.5	7.5	0.6	C312A433-30****+	0.043	10.0	10.5	6.5	7.5	0.6	C312E433-30****+	0.043	13.0	13.0	7.5	10.0	0.6	C312G433-40****+
0.047	10.0	10.5	7.0	7.5	0.6	C312A473-30****+	0.047	10.0	10.5	7.0	7.5	0.6	C312E473-30****+	0.047	13.0	13.0	8.0	10.0	0.6	C312G473-40****+
0.051	10.0	9.0	5.5	7.5	0.6	C312A513-30****+	0.051	13.0	10.0	6.0	10.0	0.6	C312E513-40****+	0.051	13.0	13.5	8.0	10.0	0.6	C312G513-40****+
0.056	10.0	9.0	5.5	7.5	0.6	C312A563-30****+	0.056	13.0	10.0	6.5	10.0	0.6	C312E563-40****+	0.056	13.0	14.0	8.5	10.0	0.6	C312G563-40****+
0.062	10.0	9.5	5.5	7.5	0.6	C312A623-30****+	0.062	13.0	10.5	6.5	10.0	0.6	C312E623-40****+	0.062	19.0	12.0	6.5	15.0	0.6	C312G623-60****+
0.068	10.0	9.5	6.0	7.5	0.6	C312A683-30****+	0.068	13.0	10.5	7.0	10.0	0.6	C312E683-40****+	0.068	19.0	13.5	6.5	15.0	0.6	C312G683-60****+
0.075	10.0	9.5	6.0	7.5	0.6	C312A753-30****+	0.075	13.0	11.0	7.0	10.0	0.6	C312E753-40****+	0.075	19.0	13.5	6.5	15.0	0.6	C312G753-60****+
0.082	10.0	10.5	6.0	7.5	0.6	C312A823-30****+	0.082	13.0	10.5	6.0	10.0	0.6	C312E823-40****+	0.082	19.0	13.5	7.0	15.0	0.6	C312G823-60****+
0.091	10.0	10.5	6.0	7.5	0.6	C312A913-30****+	0.091	13.0	11.0	6.0	10.0	0.6	C312E913-40****+	0.091	19.0	14.0	7.0	15.0	0.6	C312G913-60****+
0.10	10.0	10.5	6.5	7.5	0.6	C312A104-30****+	0.10	13.0	11.0	6.5	10.0	0.6	C312E104-40****+	0.10	19.0	14.5	7.5	15.0	0.6	C312G104-60****+
0.11	10.0	11.0	6.5	7.5	0.6	C312A114-30****+	0.11	13.0	11.0	6.5	10.0	0.6	C312E114-40****+	0.11	19.0	14.5	8.0	15.0	0.6	C312G114-60****+
0.12	10.0	11.0	6.5	7.5	0.6	C312A124-30****+	0.12	13.0	11.5	7.0	10.0	0.6	C312E124-40****+	0.12	19.0	15.0	8.0	15.0	0.6	C312G124-60****+
0.13	13.0	10.5	6.0	10.0	0.6	C312A134-40****+	0.13	19.0	12.0	6.5	15.0	0.6	C312E134-60****+	0.13	19.0	15.0	8.5	15.0	0.6	C312G134-60****+
0.15	13.0	11.0	6.5	10.0	0.6	C312A154-40****+	0.15	19.0	12.0	7.0	15.0	0.6	C312E154-60****+	0.15	19.0	15.5	9.0	15.0	0.6	C312G154-60****+
0.16	13.0	11.0	6.5	10.0	0.6	C312A164-40****+	0.16	19.0	12.5	7.0	15.0	0.6	C312E164-60****+	0.16	19.0	16.0	9.0	15.0	0.8	C312G164-60****+
0.18	13.0	12.0	6.5	10.0	0.6	C312A184-40****+	0.18	19.0	13.5	7.0	15.0	0.6	C312E184-60****+	0.18	24.0	15.0	8.0	20.0	0.8	C312G184-80****+
0.20	13.0	12.0	7.0	10.0	0.6	C312A204-40****+	0.20	19.0	14.0	7.0	15.0	0.6	C312E204-60****+	0.20	24.0	15.0	8.5	20.0	0.8	C312G204-80****+
0.22	13.0	12.5	7.0	10.0	0.6	C312A224-40****+	0.22	19.0	14.0	7.5	15.0	0.6	C312E224-60****+	0.22	24.0	16.0	8.5	20.0	0.8	C312G224-80****+
0.24	13.0	12.5	7.5	10.0	0.6	C312A244-40****+	0.24	19.0	14.5	7.5	15.0	0.6	C312E244-60****+	0.24	24.0	16.0	9.0	20.0	0.8	C312G244-80****+
0.27	13.0	13.0	7.5	10.0	0.6	C312A274-40****+	0.27	19.0	15.0	8.0	15.0	0.6	C312E274-60****+	0.27	24.0	16.5	9.5	20.0	0.8	C312G274-80****+
0.30	19.0	11.5	6.5	15.0	0.6	C312A304-60****+	0.30	19.0	15.0	8.5	15.0	0.6	C312E304-60****+	0.30	24.0	17.0	10.0	20.0	0.8	C312G304-80****+
0.33	19.0	12.0	6.5	15.0	0.6	C312A334-60****+	0.33	19.0	15.5	9.0	15.0	0.6	C312E334-60****+	0.33	24.0	17.5	10.0	20.0	0.8	C312G334-80****+
0.36	19.0	12.0	7.0	15.0	0.6	C312A364-60****+	0.36	24.0	14.0	8.5	20.0	0.8	C312E364-80****+	0.36	29.0	16.5	9.5	25.0	0.8	C312G364-A0****+
0.39	19.0	12.5	7.0	15.0	0.6	C312A394-60****+	0.39	24.0	14.5	8.5	20.0	0.8	C312E394-80****+	0.39	29.0	17.0	9.5	25.0	0.8	C312G394-A0****+
0.43	19.0	12.5	7.5	15.0	0.6	C312A434-60****+	0.43	24.0	15.0	8.5	20.0	0.8	C312E434-80****+	0.43	29.0	17.5	10.0	25.0	0.8	C312G434-A0****+
0.47	19.0	13.0	7.5	15.0	0.6	C312A474-60****+	0.47	24.0	15.0	9.0	20.0	0.8	C312E474-80****+	0.47	29.0	18.5	10.0	25.0	0.8	C312G474-A0****+
0.51	19.0	13.0	8.0	15.0	0.6	C312A514-60****+	0.51	24.0	15.5	9.5	20.0	0.8	C312E514-80****+	0.51	29.0	19.0	10.5	25.0	0.8	C312G514-A0****+
0.56	19.0	13.5	8.0	15.0	0.6	C312A564-60****+	0.56	24.0	16.0	10.0	20.0	0.8	C312E564-80****+	0.56	29.0	19.5	11.0	25.0	0.8	C312G564-A0****+
0.62	19.0	13.5	8.5	15.0	0.6	C312A624-60****+	0.62	24.0	16.5	10.0	20.0	0.8	C312E624-80****+	0.62	29.0	20.0	11.5	25.0	0.8	C312G624-A0****+
0.68	19.0	14.0	9.0	15.0	0.6	C312A684-60****+	0.68	24.0	17.5	10.5	20.0	0.8	C312E684-80****+	0.68	29.0	19.5	12.0	25.0	0.8	C312G684-A0****+
0.75	19.0	14.5	9.5	15.0	0.8	C312A754-60****+	0.75	24.0	18.0	11.0	20.0	0.8	C312E754-80****+	0.75	29.0	21.0	12.5	25.0	0.8	C312G754-A0****+
0.82	19.0	15.0	9.5	15.0	0.8	C312A824-60****+	0.82	24.0	18.5	11.5	20.0	0.8	C312E824-80****+	0.82	34.0	20.5	12.0	30.0	0.8	C312G824-C0****+
0.91	24.0	15.0	8.5	20.0	0.8	C312A914-80****+	0.91	24.0	19.0	12.0	20.0	0.8	C312E914-80****+	0.91	34.0	21.0	12.5	30.0	0.8	C312G914-C0****+
1.0	24.0	15.5	8.5	20.0	0.8	C312A105-80****+	1.0	29.0	17.5	9.0	25.0	0.8	C312E105-A0****+	1.0	34.0	21.5	13.0	30.0	0.8	C312G105-C0****+
1.1	24.0	16.0	9.0	20.0	0.8	C312A115-80****+	1.1	29.0	18.0	9.5	25.0	0.8	C312E115-A0****+							
1.2	24.0	16.0	9.5	20.0	0.8	C312A125-80****+	1.2	29.0	18.0	10.0	25.0	0.8	C312E125-A0****+							
1.3	24.0	16.5	9.5	20.0	0.8	C312A135-80****+	1.3	29.0	18.5	10.0	25.0	0.8	C312E135-A0****+							
1.5	24.0	17.0	10.5	20.0	0.8	C312A155-80****+	1.5	29.0	19.5	11.0	25.0	0.8	C312E155-A0****+							
1.6	24.0	17.5	11.0	20.0	0.8	C312A165-80****+	1.6	29.0	20.5	10.5	25.0	0.8	C312E165-A0****+							
1.8	24.0	18.0	11.5	20.0	0.8	C312A185-80****+	1.8	29.0	21.5	11.5	25.0	0.8	C312E185-A0****+							
2.0	29.0	17.5	10.5	25.0	0.8	C312A205-A0****+	2.0	29.0	22.0	12.0	25.0	0.8	C312E205-A0****+							
2.2	29.0	18.0	11.0	25.0	0.8	C312A225-A0****+	2.2	29.0	22.5	12.5	25.0	0.8	C312E225-A0****+							
2.4	29.0	18.5	11.5	25.0	0.8	C312A245-A0****+	2.4	29.0	23.0	13.0	25.0	0.8	C312E245-A0****+							
2.7	29.0	20.0	11.5	25.0	0.8	C312A275-A0****+	2.7	29.0	24.0	14.0	25.0	0.8	C312E275-A0****+							
3.0																				

■ 外形尺寸 Dimensions (mm)
Pattern I (High performance)

630Vdc(220Vac) [@]							630Vdc(220Vac) [@]							1 000Vdc(400Vac)						
C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number	C _N (μF)	W max	H max	T max	P	d	Part number
0.0010	10.0	9.0	5.5	7.5	0.6	C312J102-30****++	0.024	19.0	12.0	6.5	15.0	0.6	C312J243-60****++	0.0010	10.0	9.0	5.5	7.5	0.6	C313A102-30****++
0.0011	10.0	9.0	5.5	7.5	0.6	C312J112-30****++	0.027	19.0	12.0	7.0	15.0	0.6	C312J273-60****++	0.0011	10.0	9.0	5.5	7.5	0.6	C313A112-30****++
0.0012	10.0	9.0	5.0	7.5	0.6	C312J122-30****++	0.030	19.0	12.5	7.0	15.0	0.6	C312J303-60****++	0.0012	10.0	9.0	5.0	7.5	0.6	C313A122-30****++
0.0013	10.0	9.0	5.0	7.5	0.6	C312J132-30****++	0.033	19.0	12.5	7.5	15.0	0.6	C312J333-60****++	0.0013	10.0	9.0	5.0	7.5	0.6	C313A132-30****++
0.0015	10.0	9.0	5.0	7.5	0.6	C312J152-30****++	0.036	19.0	13.0	8.0	15.0	0.6	C312J363-60****++	0.0015	10.0	9.0	5.0	7.5	0.6	C313A152-30****++
0.0016	10.0	9.0	5.5	7.5	0.6	C312J162-30****++	0.039	19.0	13.0	8.0	15.0	0.6	C312J393-60****++	0.0016	10.0	9.0	5.5	7.5	0.6	C313A162-30****++
0.0018	10.0	9.0	5.5	7.5	0.6	C312J182-30****++	0.043	19.0	13.5	8.0	15.0	0.6	C312J433-60****++	0.0018	10.0	9.0	5.5	7.5	0.6	C313A182-30****++
0.0020	10.0	9.0	5.5	7.5	0.6	C312J202-30****++	0.047	19.0	13.5	8.5	15.0	0.6	C312J473-60****++	0.0020	10.0	9.0	5.5	7.5	0.6	C313A202-30****++
0.0022	10.0	9.0	6.0	7.5	0.6	C312J222-30****++	0.051	19.0	14.0	9.0	15.0	0.8	C312J513-60****++	0.0022	10.0	9.0	6.0	7.5	0.6	C313A222-30****++
0.0024	10.0	9.0	5.0	7.5	0.6	C312J242-30****++	0.056	19.0	15.0	8.5	15.0	0.8	C312J563-60****++	0.0024	10.0	10.0	6.0	7.5	0.6	C313A242-30****++
0.0027	10.0	9.0	5.0	7.5	0.6	C312J272-30****++	0.062	19.0	15.5	9.0	15.0	0.8	C312J623-60****++	0.0027	10.0	10.0	6.0	7.5	0.6	C313A272-30****++
0.0030	10.0	9.0	5.0	7.5	0.6	C312J302-30****++	0.068	24.0	14.5	8.0	20.0	0.8	C312J683-80****++	0.0030	10.0	10.0	6.5	7.5	0.6	C313A302-30****++
0.0033	10.0	9.0	5.5	7.5	0.6	C312J332-30****++	0.075	24.0	15.0	8.0	20.0	0.8	C312J753-80****++	0.0033	10.0	10.0	6.5	7.5	0.6	C313A332-30****++
0.0036	10.0	9.0	5.5	7.5	0.6	C312J362-30****++	0.082	24.0	15.0	8.5	20.0	0.8	C312J823-80****++	0.0036	10.0	10.5	7.0	7.5	0.6	C313A362-30****++
0.0039	10.0	9.0	5.5	7.5	0.6	C312J392-30****++	0.091	24.0	15.5	8.5	20.0	0.8	C312J913-80****++	0.0039	10.0	10.5	7.0	7.5	0.6	C313A392-30****++
0.0043	10.0	9.5	6.0	7.5	0.6	C312J432-30****++	0.10	24.0	16.0	9.0	20.0	0.8	C312J104-80****++	0.0043	10.0	10.5	7.0	7.5	0.6	C313A432-30****++
0.0047	10.0	9.5	6.0	7.5	0.6	C312J472-30****++	0.11	24.0	16.0	9.5	20.0	0.8	C312J114-80****++	0.0047	10.0	11.0	7.5	7.5	0.6	C313A472-30****++
0.0051	10.0	9.5	6.5	7.5	0.6	C312J512-30****++	0.12	24.0	16.5	10.0	20.0	0.8	C312J124-80****++	0.0051	10.0	11.0	7.5	7.5	0.6	C313A512-30****++
0.0056	10.0	10.0	6.5	7.5	0.6	C312J562-30****++	0.13	24.0	17.0	10.0	20.0	0.8	C312J134-80****++	0.0056	10.0	11.5	8.0	7.5	0.6	C313A562-30****++
0.0062	10.0	10.0	6.5	7.5	0.6	C312J622-30****++	0.15	24.0	17.5	10.5	20.0	0.8	C312J154-80****++	0.0062	10.0	11.5	8.5	7.5	0.6	C313A622-30****++
0.0068	12.5	9.0	5.5	10.0	0.6	C312J682-40****++	0.16	24.0	18.0	11.0	20.0	0.8	C312J164-80****++	0.0068	12.5	10.5	7.0	10.0	0.6	C313A682-40****++
0.0075	12.5	9.0	6.0	10.0	0.6	C312J752-40****++	0.18	24.0	19.5	11.0	20.0	0.8	C312J184-80****++	0.0075	12.5	10.5	7.0	10.0	0.6	C313A752-40****++
0.0082	12.5	9.0	6.0	10.0	0.6	C312J822-40****++	0.20	29.0	19.0	10.0	25.0	0.8	C312J204-A0****++	0.0082	12.5	10.5	7.0	10.0	0.6	C313A822-40****++
0.0091	12.5	9.5	6.0	10.0	0.6	C312J912-40****++	0.22	29.0	19.5	10.0	25.0	0.8	C312J224-A0****++	0.0091	12.5	11.0	7.5	10.0	0.6	C313A912-40****++
0.010	13.0	11.0	6.0	10.0	0.6	C312J103-40****++	0.24	29.0	20.0	10.5	25.0	0.8	C312J244-A0****++							
0.011	13.0	11.5	6.5	10.0	0.6	C312J113-40****++	0.27	29.0	20.5	11.5	25.0	0.8	C312J274-A0****++							
0.012	13.0	11.5	6.5	10.0	0.6	C312J123-40****++	0.30	29.0	21.5	11.5	25.0	0.8	C312J304-A0****++							
0.013	13.0	11.5	7.0	10.0	0.6	C312J133-40****++	0.33	29.0	22.0	12.0	25.0	0.8	C312J334-A0****++							
0.015	13.0	12.0	7.0	10.0	0.6	C312J153-40****++	0.36	29.0	22.5	12.5	25.0	0.8	C312J364-A0****++							
0.016	13.0	12.0	7.5	10.0	0.6	C312J163-40****++	0.39	34.0	20.5	12.5	30.0	0.8	C312J394-C0****++							
0.018	13.0	13.0	7.5	10.0	0.6	C312J183-40****++	0.43	34.0	21.5	13.0	30.0	0.8	C312J434-C0****++							
0.020	13.0	13.5	8.0	10.0	0.6	C312J203-40****++	0.47	34.0	22.0	13.5	30.0	0.8	C312J474-C0****++							
0.022	13.0	13.5	8.0	10.0	0.6	C312J223-40****++	0.51	34.0	22.5	14.0	30.0	0.8	C312J514-C0****++							
							0.56	34.0	23.0	14.5	30.0	0.8	C312J564-C0****++							

备注: 1. “-”表示容量偏差。 “-”=capacitance tolerance code, M=±20%,K=±10%,J=±5%
2. “****”表示引线加工和包装代码(见表1)。“****”=lead form and packing code(refer to table 1)
3. “@” Not suitable for across-the-line applications. Pls refer to Interference Suppression Capacitors(Pag.118)